

Remote Annunciator System 12VDC, 110dB, Pipe/Wall mounting

Model: HORN-LITE

Hooter:

- Operating Voltage: 12V DC
- Input Power: 10W RMS/ 13W Impedance: 8 Ohms.
- Optimized Frequency: 300-5000 Hz
- Audible Sound output: SPL at 1KHz, 110dB/10W/1m

Indicating Lamp:

- Alarm Indicating Flashing light Sun light visible (360° View)
- Light Intensity: approximately 600 to 630nM
- Operating temperature range: Up to 70 Deg. C
- Sealed water-proof unit conforming to IP65 standard.
- Weatherproof Casing with sealed toughened Type A Glass Red Colour



Enclosure:

- Die cast Aluminium alloy for longer and Maintenance free performance.
- Two Cable Entries of M20 X 1.5 with 2 PVC cable glands in bottom.
- Suitable for outdoor Installation. Resistant to UV light and direct sunlight.
- Numbers of Earthing points: 2 outside & 1 inside of enclosure.
- Mounting: With MS pipe mount bracket suitable to 2' to 4" Pipe
- Wall Mounting Hole PCD: approx. 140mm (+/- 5mm).
- Colour: Customized to Jio-BP theme.
- All necessary hardware for mounting.



**Acknowledgement
Switch Box**

ACK Switch:

- Remote Push Button with NO element suitable for outdoor use with Silicon cover on top, enclosed in Aluminium housing with 1 cable entry of M20 X 1.5 with PVC cable gland, with fixing accessories.

Electrical Connections:

- 5 Pin connectors for Flash-lite, Hooter & ACK switch.

Fasteners:

- All Fasters used on and in the units are of Stainless Steel for long lift performance.

Packaging:

- Corrugated box/ 1 Unit.

OMISOL PRIVATE LIMITED

Address: 722/2, Near Siyaram, Somanth Road, Dabhel, Daman-396210, DN&DD, India. Email:

Info@omisol.in